

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: 0.1M Tetra-n-butylammonium hydroxide in toluene/methanol  
Cat No. : J/8750/08, J/8750/15, J/8750/17, J/8750/24

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road, Loughborough,  
Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaaan 3a  
2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

Tel: 01509 231166  
Chemtrec US: (800) 424-9300  
Chemtrec EU: 001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

##### Physical hazards

Flammable liquids Category 2 (H225)

##### Health hazards

Aspiration Toxicity Category 1 (H304)  
Acute oral toxicity Category 4 (H302)

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

Acute dermal toxicity	Category 4 (H312)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Reproductive Toxicity	Category 2 (H361d)
Specific target organ toxicity - (single exposure)	Category 1 (H370)
	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
<b>Environmental hazards</b>	
Chronic aquatic toxicity	Category 3 (H412)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

- H225 - Highly flammable liquid and vapor
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H318 - Causes serious eye damage
- H370 - Causes damage to organs
- H336 - May cause drowsiness or dizziness
- H361d - Suspected of damaging the unborn child
- H373 - May cause damage to organs through prolonged or repeated exposure
- H412 - Harmful to aquatic life with long lasting effects
- H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled

## Precautionary Statements

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 - Immediately call a POISON CENTER or doctor/physician

## 2.3. Other hazards

- Toxic to terrestrial vertebrates
- This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl alcohol	67-56-1	200-659-6	17	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Toluene	108-88-3	203-625-9	80	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373) Aquatic Chronic 3 (H412)
1-Butanaminium, N,N,N-tributyl-, hydroxide	2052-49-5	218-147-6	3	Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Components	Reach Registration Number
Toluene	01-2119471310-51
Methanol	01-2119433307-44

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
<b>Ingestion</b>	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. Risk of serious damage to the lungs (by aspiration).
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Causes severe eye damage. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

## 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

re-use. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

**Technical Rules for Hazardous Substances (TRGS) 510**      Class 3  
**Storage Class (LGK) (Germany)**

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl alcohol	WEL - TWA: 200 ppm TWA; 266 mg/m <sup>3</sup> TWA WEL - STEL: 250 ppm STEL; 333 mg/m <sup>3</sup> STEL	TWA: 200 ppm 8 hr TWA: 260 mg/m <sup>3</sup> 8 hr Skin	TWA: 200 ppm 8 hr. TWA: 260 mg/m <sup>3</sup> 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m <sup>3</sup> 15 min Skin
Toluene	STEL: 100 ppm 15 min STEL: 384 mg/m <sup>3</sup> 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m <sup>3</sup> 8 hr Skin	TWA: 50 ppm (8hr) TWA: 192 mg/m <sup>3</sup> (8hr) STEL: 100 ppm (15min) STEL: 384 mg/m <sup>3</sup> (15min) Skin	TWA: 192 mg/m <sup>3</sup> 8 hr. TWA: 50 ppm 8 hr. STEL: 384 mg/m <sup>3</sup> 15 min STEL: 100 ppm 15 min Skin

#### Biological limit values

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

Workers; See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Toluene 108-88-3 ( 80 )				8.13 mg/kg bw/day

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl alcohol 67-56-1 ( 17 )		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day
Toluene 108-88-3 ( 80 )				DNEL = 384mg/kg bw/day
1-Butanaminium, N,N,N-tributyl-, hydroxide 2052-49-5 ( 3 )				DNEL = 1.4mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl alcohol 67-56-1 ( 17 )	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

Toluene 108-88-3 ( 80 )	DNEL = 384mg/m <sup>3</sup>	DNEL = 384mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>
1-Butanaminium, N,N,N-tributyl-, hydroxide 2052-49-5 ( 3 )				DNEL = 4.93mg/m <sup>3</sup>

## Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methyl alcohol 67-56-1 ( 17 )	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw
Toluene 108-88-3 ( 80 )	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg soil dw
1-Butanaminium, N,N,N-tributyl-, hydroxide 2052-49-5 ( 3 )	PNEC = 16.5µg/L	PNEC = 2.16mg/kg sediment dw	PNEC = 0.165mg/L	PNEC = 28.4mg/L	PNEC = 0.421mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol 67-56-1 ( 17 )	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
Toluene 108-88-3 ( 80 )	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw			
1-Butanaminium, N,N,N-tributyl-, hydroxide 2052-49-5 ( 3 )	PNEC = 1.65µg/L	PNEC = 0.216mg/kg sediment dw	PNEC = 16.5µg/L		

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

#### Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

<b>Large scale/emergency use</b>	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced <b>Recommended Filter type:</b> low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387
<b>Small scale/Laboratory use</b>	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. <b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
<b>Environmental exposure controls</b>	Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<b>Physical State</b>	Liquid	
<b>Appearance</b>	Colorless	
<b>Odor</b>	aromatic	
<b>Odor Threshold</b>	No data available	
<b>Melting Point/Range</b>	No data available	
<b>Softening Point</b>	No data available	
<b>Boiling Point/Range</b>	No information available	
<b>Flammability (liquid)</b>	Highly flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 1.2 vol% <b>Upper</b> 44 vol%	
<b>Flash Point</b>	4 °C / 39.2 °F	<b>Method -</b> No information available
<b>Autoignition Temperature</b>	455 °C / 851 °F	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	Not applicable	
<b>Viscosity</b>	No data available	
<b>Water Solubility</b>	Immiscible	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Methyl alcohol	-0.74	
Toluene	2.73	
1-Butanaminium, N,N,N-tributyl-, hydroxide	1.518	
<b>Vapor Pressure</b>	128 hPa @ 20°C1	
<b>Density / Specific Gravity</b>	0.850	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No information available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

### 9.2. Other information

<b>Explosive Properties</b>	Vapors may form explosive mixtures with air
-----------------------------	---

## SECTION 10: STABILITY AND REACTIVITY

<b>10.1. Reactivity</b>	None known, based on information available
<b>10.2. Chemical stability</b>	Stable under normal conditions.

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

## 10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.  
**Hazardous Reactions** None under normal processing.

## 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

## 10.5. Incompatible materials

Acids. Acid anhydrides. Acid chlorides. Metals. Reducing Agent.

## 10.6. Hazardous decomposition products

Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

(a) acute toxicity;  
**Oral** Category 4  
**Dermal** Category 4  
**Inhalation** Category 4

#### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h
1-Butanaminium, N,N,N-tributyl-, hydroxide	500 mg/kg (Rat)	-	-

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;  
**Respiratory** No data available  
**Skin** No data available

Component	Test method	Test species	Study result
Methyl alcohol 67-56-1 (17)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available  
There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

Component	Test method	Test species / Duration	Study result
Methyl alcohol 67-56-1 (17)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

**Developmental Effects** Possible risk of harm to the unborn child.  
**Teratogenicity** Teratogenic effects have occurred in experimental animals.



# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

(h) STOT-single exposure; Category 1  
Category 3

**Results / Target organs** Central nervous system (CNS), Optic nerve.

(i) STOT-repeated exposure; Category 2

**Target Organs** Neuropsychological effects, Eyes, Ears.

(j) aspiration hazard; Category 1

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)

Component	Microtox	M-Factor
Methyl alcohol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
Toluene	EC50 = 19.7 mg/L 30 min	

### 12.2. Persistence and degradability

#### Persistence

Persistence is unlikely, Immiscible with water.

Component	Degradability
Methyl alcohol 67-56-1 ( 17 )	DT50 ~ 17.2d >94% after 20d
Toluene 108-88-3 ( 80 )	86% (20d)

#### Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### 12.3. Bioaccumulative potential

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless
Toluene	2.73	90
1-Butanaminium, N,N,N-tributyl-, hydroxide	1.518	No data available

### 12.4. Mobility in soil

The product is insoluble and floats on water Spillage unlikely to penetrate soil Is not likely

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

mobile in the environment due its low water solubility.

## 12.5. Results of PBT and vPvB assessment

No data available for assessment.

## 12.6. Endocrine disrupting properties

### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

## 12.7. Other adverse effects

### Persistent Organic Pollutant

This product does not contain any known or suspected substance

### Ozone Depletion Potential

This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Do not let this chemical enter the environment.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

#### 14.1. UN number

UN1993

#### 14.2. UN proper shipping name

Flammable liquid, n.o.s.

#### Technical Shipping Name

Contains toluene and methanol

#### 14.3. Transport hazard class(es)

3

#### 14.4. Packing group

II

### ADR

#### 14.1. UN number

UN1993

#### 14.2. UN proper shipping name

Flammable liquid, n.o.s.

#### Technical Shipping Name

Contains toluene and methanol

#### 14.3. Transport hazard class(es)

3

#### 14.4. Packing group

II

### IATA

#### 14.1. UN number

UN1993

#### 14.2. UN proper shipping name

Flammable liquid, n.o.s.

#### Technical Shipping Name

Contains toluene and methanol

#### 14.3. Transport hazard class(es)

3

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

- 14.4. Packing group** II
- 14.5. Environmental hazards** No hazards identified
- 14.6. Special precautions for user** No special precautions required.
- 14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl alcohol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
Toluene	108-88-3	203-625-9	-	-	X	X	KE-33936	X	X
1-Butanaminium, N,N,N-tributyl-, hydroxide	2052-49-5	218-147-6	-	-	X	X	KE-34029	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl alcohol	67-56-1	X	ACTIVE	X	-	X	X	X
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X
1-Butanaminium, N,N,N-tributyl-, hydroxide	2052-49-5	X	ACTIVE	X	-	X	X	X

**Legend:** X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
1-Butanaminium, N,N,N-tributyl-, hydroxide	2052-49-5	-	-	-

#### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

#### Seveso III Directive (2012/18/EC)

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Toluene	108-88-3	Not applicable	Not applicable
1-Butanaminium, N,N,N-tributyl-, hydroxide	2052-49-5	Not applicable	Not applicable

**Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals**

Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl alcohol	WGK 2	Class I : 20 mg/m <sup>3</sup> (Massenkonzentration)
Toluene	WGK3	
1-Butanaminium, N,N,N-tributyl-, hydroxide	WGK1	

Component	France - INRS (Tables of occupational diseases)
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl alcohol 67-56-1 ( 17 )	Prohibited and Restricted Substances	Group I	
Toluene 108-88-3 ( 80 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H332 - Harmful if inhaled

# SAFETY DATA SHEET

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H370 - Causes damage to organs  
H336 - May cause drowsiness or dizziness  
H361d - Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H412 - Harmful to aquatic life with long lasting effects  
H225 - Highly flammable liquid and vapor  
H226 - Flammable liquid and vapor  
H301 - Toxic if swallowed  
H311 - Toxic in contact with skin  
H314 - Causes severe skin burns and eye damage  
H331 - Toxic if inhaled

## Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

**Creation Date** 19-Jan-2015

**Revision Date** 09-Feb-2024

**Revision Summary** Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

# **SAFETY DATA SHEET**

0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Revision Date 09-Feb-2024

---

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**