

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 21-Apr-2014 Revision Date 10-Feb-2024 **Revision Number** 6

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

1.1. Product identifier

Product Description: 2-Methyl-2-butanol

Cat No.: A18304

tert-Amyl alcohol Synonyms

CAS No 75-85-4 200-908-9 EC No Molecular Formula C5 H12 O

REACH registration number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

PC21 - Laboratory chemicals **Product category**

PROC15 - Use as a laboratory reagent **Process categories**

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY. United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number US:001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No. US:001-800-424-9300 / Europe:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

ALFAAA18304

2-Methyl-2-butanol Revision Date 10-Feb-2024

Flammable liquids Category 2 (H225)

Health hazards

Acute dermal toxicity
Acute Inhalation Toxicity - Vapors
Category 4 (H312)
Category 4 (H332)
Skin Corrosion/Irritation
Category 2 (H315)
Serious Eye Damage/Eye Irritation
Category 1 (H318)
Specific target organ toxicity - (single exposure)
Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H312 + H332 - Harmful in contact with skin or if inhaled

Precautionary Statements

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to
Component	CASINO		I WEIGHT /0	I CLP Classification - According to

2-Methyl-2-butanol Revision Date 10-Feb-2024

				GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
2-Methyl-2-butanol	75-85-4	EEC No. 200-908-9	>95	Flam. Liq. 2 (H225) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335) STOT SE 3 (H336)

REACH registration number -

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe eye damage. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

2-Methyl-2-butanol Revision Date 10-Feb-2024

Carbon monoxide (CO), Carbon dioxide (CO2).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Protect from light. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

2-Methyl-2-butanol Revision Date 10-Feb-2024

Exposure limits

List source(s):

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

Workers; See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
2-Methyl-2-butanol				DNEL = 2.5mg/kg
75-85-4 (>95)				bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
2-Methyl-2-butanol 75-85-4 (>95)			DNEL = 267.8mg/m ³	DNEL = 17.2mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

ſ	Component	Fresh water			Water Intermittent Microorganisms in	
			sediment		sewage treatment	
Ī	2-Methyl-2-butanol	PNEC = 0.5mg/L	PNEC = 2.01 mg/kg	PNEC = 5mg/L	PNEC = 10mg/L	PNEC =
L	75-85-4 (>95)		sediment dw			0.108mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
2-Methyl-2-butanol	PNEC = 0.05mg/L	PNEC =			
75-85-4 (>95)		0.201mg/kg			
		sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material Natural rubber Nitrile rubber Neoprene	Breakthrough time See manufacturers recommendations	Glove thickness	EU standard EN 374	Glove comments (minimum requirement)
PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g.

2-Methyl-2-butanol Revision Date 10-Feb-2024

sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection**

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Small scale/Laboratory use Maintain adequate ventilation

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Colorless **Appearance** Odor Strong

No data available **Odor Threshold** -12 °C / 10.4 °F **Melting Point/Range Softening Point** No data available

Boiling Point/Range 102 °C / 215.6 °F @ 760 mmHg Flammability (liquid) On basis of test data Highly flammable Liquid

Flammability (solid,gas) Not applicable

Explosion Limits Lower 1.3 Vol%

Upper 9.6 Vol%

Flash Point 20 °C / 68 °F Method - No information available

Autoignition Temperature 435 °C / 815 °F **Decomposition Temperature** No data available

рΗ 6.0 118 g/L ag.sol

Viscosity 3.7 mPa s at 25 °C 70.7 g/L (25°C) **Water Solubility**

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

log Pow Component 2-Methyl-2-butanol 0.77

15.5 hPa @ 20 °C **Vapor Pressure**

Density / Specific Gravity 0.800

Bulk Density Not applicable Liquid **Vapor Density** 3.04 (Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C5 H12 O **Molecular Weight** 88.15

Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Revision Date 10-Feb-2024 2-Methyl-2-butanol

10.2. Chemical stability

Light sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization

Hazardous polymerization does not occur.

Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

Excess heat. Exposure to light.

10.5. Incompatible materials

Strong oxidizing agents. Metals.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Based on available data, the classification criteria are not met Oral

Dermal Category 4 Inhalation Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-Methyl-2-butanol	5184 mg/kg (Rat)	1720 mg/kg (Rabbit)	<20.6 mg/L/6h (Rat)

(b) skin corrosion/irritation; Category 2

Category 1 (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met Skin

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

Based on available data, the classification criteria are not met (g) reproductive toxicity;

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

None known. **Target Organs**

Revision Date 10-Feb-2024 2-Methyl-2-butanol

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects Do not empty into drains. .

Component	Freshwater Fish	Water Flea	Freshwater Algae
2-Methyl-2-butanol	LC50: 2430 mg/L/48h	EC50: 540 mg/L/48h (DIN 38412	
	(Leuciscus idus melanotus)	part 11)	
	(DIN 38412 part 15)		

12.2. Persistence and degradability Not readily biodegradable

Persistence

Persistence is unlikely.

Bioaccumulation is unlikely 12.3. Bioaccumulative potential

Component	log Pow	Bioconcentration factor (BCF)
2-Methyl-2-butanol	0.77	No data available

12.4. Mobility in soil The product is water soluble, and may spread in water systems . Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects **Persistent Organic Pollutant**

Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

According to the European Waste Catalog, Waste Codes are not product specific, but **European Waste Catalogue (EWC)**

2-Methyl-2-butanol Revision Date 10-Feb-2024

application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1105 **14.2. UN proper shipping name** PENTANOLS

14.3. Transport hazard class(es) 3 14.4. Packing group II

ADR

14.1. UN number UN1105 14.2. UN proper shipping name PENTANOLS

14.3. Transport hazard class(es) 3 14.4. Packing group II

IATA

14.1. UN numberUN110514.2. UN proper shipping namePENTANOLS

14.3. Transport hazard class(es) 3 14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
2-Methyl-2-butanol	75-85-4	200-908-9	-	i	X	X	KE-23573	Χ	X
							-		

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
2-Methyl-2-butanol	75-85-4	X	ACTIVE	Х	-	X	X	X

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC

Revision Date 10-Feb-2024

2-Methyl-2-butanol

		Annex XIV - Substances Subject to Authorization		1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
2-Methyl-2-butanol	75-85-4	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -	
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report	
		Notification	Requirements	
2-Methyl-2-butanol	75-85-4	Not applicable	Not applicable	

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
2-Methyl-2-butanol	WGK1	

Component France - INRS (Tables of occupational diseases)		France - INRS (Tables of occupational diseases)
2-Methyl-2-butanol Tableaux des maladies profe		Tableaux des maladies professionnelles (TMP) - RG 84

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H312 - Harmful in contact with skin

H332 - Harmful if inhaled

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H225 - Highly flammable liquid and vapor

2-Methyl-2-butanol Revision Date 10-Feb-2024

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By Health, Safety and Environmental Department

Creation Date 21-Apr-2014 **Revision Date** 10-Feb-2024

Revision Summary New emergency telephone response service provider.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

LD50 - Lethal Dose 50%

IARC - International Agency for Research on Cancer

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

Predicted No Effect Concentration (PNEC)

TWA - Time Weighted Average

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)