

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 05-Dec-2005 Revision Date 10-Feb-2024 Revision Number 3

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: <u>2-Butyne-1,4-diol</u>

Cat No. : A14539

Synonyms 1,4-Dihydroxy-2-butyne

 Index No
 603-076-00-9

 CAS No
 110-65-6

 EC No
 203-788-6

 Molecular Formula
 C4 H6 O2

REACH registration number -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

ALFAAA14539

2-Butyne-1,4-diol Revision Date 10-Feb-2024

Based on available data, the classification criteria are not met

Health hazards

Acute oral toxicity Category 3 (H301) Acute dermal toxicity Category 3 (H311) Acute Inhalation Toxicity - Dusts and Mists Category 3 (H331) Skin Corrosion/Irritation Category 1 B (H314) Serious Eye Damage/Eye Irritation Category 1 (H318) Skin Sensitization Category 1 (H317) Specific target organ toxicity - (single exposure) Category 3 (H335) Specific target organ toxicity - (repeated exposure) Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16





Signal Word

Danger

Hazard Statements

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H335 - May cause respiratory irritation

H373 - May cause damage to organs through prolonged or repeated exposure

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

Precautionary Statements

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxicity to Soil Dwelling Organisms

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
2-Butyne-1,4-diol	110-65-6	EEC No. 203-788-6	>95	Acute Tox. 3 (H331) Acute Tox. 3 (H301) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) STOT RE 2 (H373) STOT SE 3 (H335)
Formaldehyde	50-00-0	200-001-8	0.01-0.1	Acute Tox. 3 (H301) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) STOT SE 3 (H335) Muta. 2 (H341) Carc. 1B (H350)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
2-Butyne-1,4-diol	Skin Corr. 1B :: C>=50%	-	-
	Skin Irrit. 2 :: 25%<=C<50%		
	Eye Irrit. 2 :: 25%<=C<50%		
Formaldehyde	Skin Corr. 1B :: C>=25%	-	-
	Eye Irrit. 2 :: 5%<=C<25%		
	Skin Irrit. 2 :: 5%<=C<25%		
	Skin Sens. 1 :: C>=0.2%		
	STOT SE 3 :: C>=5%		

REACH registration number			-
Components	Reach Re	gistration Number	
Formaldehyde	01-2	119488953-20	
2-Butyne-1,4-diol	01-2	119489899-05	

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If

not breathing, give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergic skin reaction. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Thermal decomposition can lead to release of irritating gases and vapors.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Evacuate personnel to safe areas. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid dust formation.

6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not ingest. If swallowed then seek immediate medical assistance. Do not breathe (dust, vapor, mist, gas). Avoid dust formation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 6.1C Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

Component	The United Kingdom	European Union	Ireland
2-Butyne-1,4-diol	STEL: 1.5 mg/m ³ 15 min	TWA: 0.5 mg/m ³ (8h)	TWA: 0.5 mg/m ³ 8 hr.
			STEL: 1.5 mg/m ³ 15 min
Formaldehyde	STEL: 2 ppm 15 min	TWA: 0.37 mg/m ³ (8h)	TWA: 0.3 ppm 8 hr.
	STEL: 2.5 mg/m ³ 15 min	TWA: 0.3 ppm (8h)	TWA: 0.5 ppm 8 hr. for the
	TWA: 2 ppm 8 hr	Skin	healthcare, funeral and
	TWA: 2.5 mg/m ³ 8 hr	STEL: 0.74 mg/m ³ (8h)	embalming sectors until July
	Carc.	STEL: 0.6 ppm (8h)	11, 2024
			TWA: 0.37 mg/m ³ 8 hr.
			TWA: 0.62 mg/m ³ 8 hr. for
			the healthcare, funeral and
			embalming sectors until July
			11, 2024
			STEL: 0.6 ppm 15 min
			STEL: 0.738 mg/m ³ 15 min
			STEL: 0.62 mg/m ³ 15 min

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

Workers; See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
2-Butyne-1,4-diol		DNEL = 6.6mg/kg		DNEL = 0.2mg/kg
110-65-6 (>95)		bw/day		bw/day
Formaldehyde			DNEL = 37µg/cm2	DNEL = 240mg/kg
50-00-0 (0.01-0.1)				bw/dav

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
2-Butyne-1,4-diol	DNEL = 1mg/m ³	$DNEL = 100 mg/m^3$	$DNEL = 0.5mg/m^3$	$DNEL = 1.25 mg/m^3$

2-Butyne-1,4-diol Revision Date 10-Feb-2024

110-65-6 (>95)			
Formaldehyde	$DNEL = 0.75 mg/m^3$	$DNEL = 0.375 mg/m^3$	DNEL = 9mg/m ³
50-00-0 (0.01-0.1)		_	

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
2-Butyne-1,4-diol	PNEC =			PNEC = 134mg/L	PNEC = 0.05mg/kg
110-65-6 (>95)	0.0155mg/L				soil dw
Formaldehyde	PNEC = 0.44mg/L	PNEC = 2.3mg/kg	PNEC = 4.44mg/L	PNEC = 0.19mg/L	PNEC = 0.2mg/kg
50-00-0 (0.01-0.1)		sediment dw			soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
2-Butyne-1,4-diol	PNEC =				
110-65-6 (>95)	0.00155mg/L				
Formaldehyde	PNEC = 0.44mg/L	PNEC = 2.3mg/kg			
50-00-0 (0.01-0.1)		sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material Nitrile rubber Neoprene Natural rubber	Breakthrough time See manufacturers recommendations	Glove thickness	EU standard EN 374	Glove comments (minimum requirement)
PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001 When RPE is used a face piece Fit Test should be conducted

Revision Date 10-Feb-2024 2-Butyne-1,4-diol

Environmental exposure controls Prevent product from entering drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Solid

Appearance Beige

Odor No information available No data available **Odor Threshold**

54 - 58 °C / 129.2 - 136.4 °F Melting Point/Range

Softening Point No data available 238 °C / 460.4 °F **Boiling Point/Range**

Flammability (liquid) Not applicable Solid

Flammability (solid,gas) No information available **Explosion Limits** No data available

152 °C / 305.6 °F Flash Point Method - No information available

410 °C / 770 °F **Autoignition Temperature Decomposition Temperature** > 150°C

100 g/L aq.sol pН 6.4

Viscosity Not applicable Solid

Water Solubility 2960 g/L (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow 2-Butyne-1,4-diol -0.73Formaldehyde -0.35

Vapor Pressure 1.33 mbar @ 102 °C

Density / Specific Gravity 1.200

Bulk Density No data available

Vapor Density Not applicable Solid

Particle characteristics No data available

9.2. Other information

C4 H6 O2 **Molecular Formula Molecular Weight** 86.09

Not applicable - Solid **Evaporation Rate**

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Finely powdered metals. Acid

anhydrides. Acid chlorides.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 3
Dermal Category 3
Inhalation Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-Butyne-1,4-diol	176 mg/kg (Rat female)	659 mg/kg (Rat)	0.69 mg/L/4h (Rat)
Formaldehyde	500 mg/kg (Rat)	LD50 = 270 mg/kg (Rabbit)	0.578 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met

Skin Category 1

Component	Test method	Test species	Study result
Formaldehyde	Skin sensitization	Man	Sensitizer
50-00-0 (0.01-0.1)	Test method Patch Test	guinea pig	Sensitization
	Respiratory sensitization		
	in vitro		

May cause sensitization by skin contact

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Formaldehyde	Carc Cat. 1B	Cat 3		Group 1

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Category 2

Revision Date 10-Feb-2024 2-Butyne-1,4-diol

Target Organs Liver, Kidney, spleen.

Not applicable (j) aspiration hazard;

Solid

delayed

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Do not empty into drains. Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
2-Butyne-1,4-diol	49.3 - 58.3 mg/L LC50 96 h	26.8 mg/L EC50 = 48 h	430 mg/L EC50 = 96 h
Formaldehyde	Leuciscus idus: LC50 = 15 mg/L	EC50 = 20 mg/L 96h	480 mg/L EC50 = 72 h EC50 (72h) = 4.89 mg/L
Í	96h	EC50 = 2 mg/L 48h	(Desmodesmus subspicatus)

Component	Microtox	M-Factor
2-Butyne-1,4-diol	EC50 = 1343 mg/L 48 h	
	EC50 = 2940 mg/L 17 h	

12.2. Persistence and degradability Readily biodegradable **Persistence** Persistence is unlikely.

Component	Degradability
Formaldehyde	Readily biodegradable (OECD guideline 301A, 301C and 301D)
50-00-0 (0.01-0.1)	under aerobic and anaerobic conditions.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
2-Butyne-1,4-diol	-0.73	3.16
Formaldehyde	-0.35	No data available

The product is water soluble, and may spread in water systems . Will likely be mobile in the 12.4. Mobility in soil

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Do not empty into drains. Large amounts will

affect pH and harm aquatic organisms.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN2716 **14.2. UN proper shipping name** 1,4-Butynediol

14.3. Transport hazard class(es) 6.1 14.4. Packing group III

ADR

14.1. UN number UN2716 **14.2 UN proper shipping name** 1 4-Butyne

14.2. UN proper shipping name 1,4-Butynediol **14.3. Transport hazard class(es)** 6.1

14.3. Transport hazard class(es) 6.1 14.4. Packing group III

<u>IATA</u>

14.1. UN number UN2716 **14.2. UN proper shipping name** U,4-Butynediol

14.3. Transport hazard class(es) 6.1 14.4. Packing group III

14.5. Environmental hazardsNo hazards identified

14.6. Special precautions for user No special precautions required.

<u>14.7. Maritime transport in bulk</u> Not applicable, packaged goods according to IMO instruments

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

2-Butyne-1,4-diol Revision Date 10-Feb-2024

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
2-Butyne-1,4-diol	110-65-6	203-788-6	-	-	X	X	X	X	X
Formaldehyde	50-00-0	200-001-8	-	-	X	X	KE-17074	Х	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
2-Butyne-1,4-diol	110-65-6	Х	ACTIVE	X	-	X	Х	X
Formaldehyde	50-00-0	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
2-Butyne-1,4-diol	110-65-6	-	Use restricted. See item 75. (see link for restriction details)	-
Formaldehyde	50-00-0	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
2-Butyne-1,4-diol	110-65-6	Not applicable	Not applicable
Formaldehyde	50-00-0	5 tonne	50 tonne

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
2-Butyne-1,4-diol	WGK 2	Class I: 20 mg/m³ (Massenkonzentration)
Formaldehyde	WGK 3	Krebserzeugende Stoffe - : 5 mg/m³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Formaldehyde	Tableaux des maladies professionnelles (TMP) - RG 43

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Formaldehyde 50-00-0 (0.01-0.1)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H373 - May cause damage to organs through prolonged or repeated exposure

H341 - Suspected of causing genetic defects

H350 - May cause cancer

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

2-Butyne-1,4-diol Revision Date 10-Feb-2024

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data
Health Hazards Calculation method
Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By Health, Safety and Environmental Department

Creation Date05-Dec-2005Revision Date10-Feb-2024

Revision Summary New emergency telephone response service provider.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet