

Creation Date 23-Nov-2009

Revision Date 21-Jan-2026

Revision Number 12

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

**Product Description:** Petroleum ether, boiling range 100-140°C  
**Cat No. :** 444360000; 444360250  
**Synonyms** Naphtha (petroleum)  
**Index No** 649-328-00-1  
**CAS No** 64742-49-0  
**EC No** 265-151-9

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Laboratory chemicals  
**Sector of use** SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites  
**Product category** PC21 - Laboratory chemicals  
**Process categories** PROC15 - Use as a laboratory reagent  
**Environmental release category** ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)  
**Uses advised against** No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
 Fisher Scientific UK  
 Bishop Meadow Road,  
 Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
 Thermo Fisher Scientific  
 Janssen Pharmaceuticaan 3a, 2440 Geel, Belgium

**E-mail address** [begele.sdsdesk@thermofisher.com](mailto:begele.sdsdesk@thermofisher.com)

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

#### Physical hazards

Flammable liquids

Category 2 (H225)

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

## Health hazards

Aspiration Toxicity  
Specific target organ toxicity - (single exposure)

Category 1 (H304)  
Category 3 (H336)

## Environmental hazards

Chronic aquatic toxicity

Category 2 (H411)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects  
EUH066 - Repeated exposure may cause skin dryness or cracking

## Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P331 - Do NOT induce vomiting  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P312 - Call a POISON CENTER or doctor if you feel unwell  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Naphtha, petroleum, hydrotreated light	64742-49-0	EEC No. 265-151-9	>95	Flam. Liq. 2 (H225) Aquatic Chronic 2 (H411)

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

				Asp. Tox. 1 (H304) STOT SE 3 (H336) (EUH066)
Cyclohexane	110-82-7	203-806-2	2	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Cyclohexane	-	1	-

## Note

UVCB Hydrocarbons

C7-C9, n-alkanes, isoalkanes, cyclics

Reach Registration Number 01-2119473851-33

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	If symptoms persist, call a physician.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	Remove to fresh air. Get medical attention. Risk of serious damage to the lungs (by aspiration). If not breathing, give artificial respiration.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

## 5.1. Extinguishing media

### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

### **Extinguishing media which must not be used for safety reasons**

No information available.

## 5.2. Special hazards arising from the substance or mixture

Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses. Extremely flammable.

### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

Technical Rules for Hazardous Substances (TRGS) 510  
Storage Class (LGK) (Germany)

Class 3

### 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Cyclohexane	STEL: 300 ppm 15 min STEL: 1050 mg/m <sup>3</sup> 15 min TWA: 100 ppm 8 hr TWA: 350 mg/m <sup>3</sup> 8 hr	TWA: 200 ppm (8hr) TWA: 700 mg/m <sup>3</sup> (8hr)	TWA: 200 ppm 8 hr. TWA: 700 mg/m <sup>3</sup> 8 hr. STEL: 600 ppm 15 min STEL: 2100 mg/m <sup>3</sup> 15 min

#### Biological limit values

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Cyclohexane 110-82-7 ( 2 )				DNEL = 2016mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Naphtha, petroleum, hydrotreated light 64742-49-0 ( >95 )	DNEL = 1066.67mg/m <sup>3</sup>	DNEL = 1286.4mg/m <sup>3</sup>	DNEL = 837.5mg/m <sup>3</sup>	
Cyclohexane 110-82-7 ( 2 )	DNEL = 1400mg/m <sup>3</sup>	DNEL = 1400mg/m <sup>3</sup>	DNEL = 700mg/m <sup>3</sup>	DNEL = 700mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Cyclohexane 110-82-7 ( 2 )	PNEC = 0.207mg/L	PNEC = 16.68mg/kg sediment dw	PNEC = 0.207mg/L	PNEC = 3.24mg/L	PNEC = 3.38mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

Cyclohexane 110-82-7 ( 2 )	PNEC = 0.207mg/L	PNEC = 16.68mg/kg sediment dw			
-------------------------------	------------------	-------------------------------------	--	--	--

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

#### Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

#### Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

#### Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

#### Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### Physical State

Liquid

#### Appearance

Colorless

#### Odor

Petroleum distillates

#### Odor Threshold

No data available

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

<b>Melting Point/Range</b>	-30 °C / -22 °F	
<b>Softening Point</b>	No data available	
<b>Boiling Point/Range</b>	100 - 140 °C / 212 - 284 °F	@ 760 mmHg
<b>Flammability (liquid)</b>	Highly flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 0.7 vol% <b>Upper</b> 7 vol%	
<b>Flash Point</b>	6 °C / 43 °F	<b>Method</b> - No information available
<b>Autoignition Temperature</b>	256 °C / 493 °F	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	No information available	
<b>Viscosity</b>	0.76 cSt @ 25°C	
<b>Water Solubility</b>	Insoluble	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Cyclohexane	3.44	
<b>Vapor Pressure</b>	27 mbar @ 20 °C	
<b>Density / Specific Gravity</b>	0.725	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No data available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

## 9.2. Other information

<b>Explosive Properties</b>	Vapors may form explosive mixtures with air
<b>Evaporation Rate</b>	> 1

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing.

### 10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

ACR44436

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

**(a) acute toxicity;**

**Oral**

Based on available data, the classification criteria are not met

**Dermal**

Based on available data, the classification criteria are not met

**Inhalation**

Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha, petroleum, hydrotreated light	LD50 > 5000 mg/kg ( Rat )	LD50 > 3160 mg/kg ( Rabbit )	LC50 = 73680 ppm ( Rat ) 4 h
Cyclohexane	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	LC50 > 32880 mg/m <sup>3</sup> ( Rat ) 4 h

**(b) skin corrosion/irritation;**

Based on available data, the classification criteria are not met

**(c) serious eye damage/irritation;**

Based on available data, the classification criteria are not met

**(d) respiratory or skin sensitization;**

**Respiratory**

Based on available data, the classification criteria are not met

**Skin**

Based on available data, the classification criteria are not met

**(e) germ cell mutagenicity;**

Based on available data, the classification criteria are not met

**(f) carcinogenicity;**

Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Naphtha, petroleum, hydrotreated light	Carc Cat. 1B			

**(g) reproductive toxicity;**

Based on available data, the classification criteria are not met

**(h) STOT-single exposure;**

Category 3

**Results / Target organs**

Central nervous system (CNS).

**(i) STOT-repeated exposure;**

Based on available data, the classification criteria are not met

**Target Organs**

None known.

**(j) aspiration hazard;**

Category 1

**Symptoms / effects, both acute and delayed**

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

**Endocrine Disrupting Properties**

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecotoxicity effects**

The product contains following substances which are hazardous for the environment. Toxic

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Naphtha, petroleum, hydrotreated light	LC50: = 8.41 mg/L, 96h semi-static, closed (Oncorhynchus mykiss)		
Cyclohexane	LC50: 48.87 - 68.76 mg/L, 96h static (Poecilia reticulata) LC50: 24.99 - 44.69 mg/L, 96h static (Lepomis macrochirus) LC50: 23.03 - 42.07 mg/L, 96h static (Pimephales promelas) LC50: 3.96 - 5.18 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 0.9 mg/l/48h	EC50 >500 mg/L/72h

Component	Microtox	M-Factor
Cyclohexane	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	1

## 12.2. Persistence and degradability

**Persistence** Insoluble in water, Persistence is unlikely, based on information available.

Component	Degradability
Cyclohexane 110-82-7 ( 2 )	77% (28d)

**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

## 12.3. Bioaccumulative potential

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Cyclohexane	3.44	83.15

## 12.4. Mobility in soil

Spillage unlikely to penetrate soil The product is insoluble and floats on water The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Is not likely mobile in the environment due its low water solubility. Will likely be mobile in the environment due to its volatility.

## 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

## 12.6. Endocrine disrupting properties

### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

## 12.7. Other adverse effects

### Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from Residues/Unused

Waste is classified as hazardous. Dispose of in accordance with the European Directives

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

<b>Products</b>	on waste and hazardous waste. Dispose of in accordance with local regulations.
<b>Contaminated Packaging</b>	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
<b>European Waste Catalogue (EWC)</b>	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
<b>Other Information</b>	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

<b>14.1. UN number</b>	UN3295
<b>14.2. UN proper shipping name</b>	Hydrocarbons, liquid, n.o.s.
<b>Technical Shipping Name</b>	Petroleum ether, boiling range 100-140°C
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

### ADR

<b>14.1. UN number</b>	UN3295
<b>14.2. UN proper shipping name</b>	Hydrocarbons, liquid, n.o.s.
<b>Technical Shipping Name</b>	Petroleum ether, boiling range 100-140°C
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

### IATA

<b>14.1. UN number</b>	UN3295
<b>14.2. UN proper shipping name</b>	Hydrocarbons, liquid, n.o.s.
<b>Technical Shipping Name</b>	Petroleum ether, boiling range 100-140°C
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

<b>14.5. Environmental hazards</b>	Dangerous for the environment Product is a marine pollutant according to the criteria set by IMDG/IMO
<b>14.6. Special precautions for user</b>	No special precautions required.
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

(AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Naphtha, petroleum, hydrotreated light	64742-49-0	265-151-9	-	-	X	X	KE-25623	-	-
Cyclohexane	110-82-7	203-806-2	-	-	X	X	KE-18562	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Naphtha, petroleum, hydrotreated light	64742-49-0	X	ACTIVE	X	-	X	X	X
Cyclohexane	110-82-7	X	ACTIVE	X	-	X	X	X

**Legend:** X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Naphtha, petroleum, hydrotreated light	64742-49-0	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 29. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Cyclohexane	110-82-7	-	Use restricted. See entry 57. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Naphtha, petroleum, hydrotreated light	64742-49-0	2500 tonne	25000 tonne
Cyclohexane	110-82-7	Not applicable	Not applicable

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Basel Convention (Hazardous Waste)
Naphtha, petroleum, hydrotreated light	64742-49-0	Listed	Not applicable	Not applicable
Cyclohexane	110-82-7	Listed	Not applicable	Not applicable

**Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals**

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Naphtha, petroleum, hydrotreated light	WGK2	
Cyclohexane	WGK2	

Component	France - INRS (Tables of occupational diseases)
Naphtha, petroleum, hydrotreated light	Tableaux des maladies professionnelles (TMP) - RG 84
Cyclohexane	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Cyclohexane 110-82-7 ( 2 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H411 - Toxic to aquatic life with long lasting effects

EUH066 - Repeated exposure may cause skin dryness or cracking

### Legend

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-140°C

Revision Date 21-Jan-2026

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**Key literature references and sources for data**

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

## Training Advice

Chemical incident response training.

**Creation Date**

23-Nov-2009

**Revision Date**

21-Jan-2026

**Revision Summary**

Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**